

Private Label

Premium Inkjet Media



CV610RF Repositionable Wall Fabric

Repositionable Lo-Tac Wall Fabric with an applied proprietary inkjet micro-porous coating. Compatible with dye and pigment aqueous inks although pigments are recommended to resist fading. Water resistant after drying. Works on all popular brands of aqueous wide format inkjet printers. This product is removable, reusable and repositionable. Sticks to virtually any painted surface in all weather and room temperatures, and can be easily removed residue free. The material does not rip or wrinkle and is not required to be removed over a certain period of time. Not recommended for rough painted surfaces including stucco, brick, non-painted cement surfaces, or heavy painted spackled board. Allow 30 days for newly painted surfaces.

White Point	94.0 0.0 0.0	CIE L*a*b* D50/2°
Gloss/Finish	matte	
Weight	240 gsm	+/- 5
Thickness	7 mil	12 mil with backer
Opacity	99%	
Durability	6 months	Outdoors without lamination
Standard Widths	42" (100' length on 2" core)	
Compatibility	Aqueous inkjet, dye and pigment	

The information above is derived from internal testing by our company and based on information received from our suppliers. The values shown are for reference only, and are provided without guaranty and do not constitute a warranty, expressed or implied. The purchaser should determine, prior to use, the suitability of this material for his/her specific purpose. Data represents an average and is not intended for use as a specification.